


REMARKS

Early and favorable acceptance of this continuation application is respectfully requested.

Respectfully submitted,

BAKER BOTTS L.L.P.
Attorneys for Applicant



Douglas M. Kuehl
Registration No. 41,915

Date: June 18, 2002

CORRESPONDENCE ADDRESS:

Douglas, M. Kuehl, Esq.
Baker Botts L.L.P.
2001 Ross Avenue
Dallas, Texas 75201
Phone: (214) 953-6486

2005472-061802

MARKED-UP VERSION OF THE CLAIMS

1. A multi-stage optical amplifier, comprising:
an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber configured to be coupled to a signal source that produces a plurality of signal wavelengths λ_s , and a pump source that produces one or more pump wavelengths λ_p , wherein the one or more pump wavelengths λ_p are less than at least a portion of the plurality of signal wavelengths λ_s , at least a portion of the plurality of signal wavelengths λ_s of the first Raman amplifier fiber having an optical noise figure of less than 8 dB and less than an optical noise figure of the second Raman amplifier fiber, and at least a portion of the plurality of signal wavelengths λ_s of the second Raman amplifier fiber having a gain level of at least 5 dB;
a signal input port coupled to the optical fiber;
a signal output port coupled to the optical fiber;
a pump input port coupled to the optical fiber;
a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction; and
a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber.
2. The multi-stage optical amplifier of claim 1, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.
3. The multi-stage optical amplifier of claim 1, wherein the pump shunt is coupled to the signal input port and the signal output port.
4. The multi-stage optical amplifier of claim 1, further comprising:
a distributed Raman amplifier coupled to the signal input port.

5. The multi-stage optical amplifier of claim 4, wherein at least a portion of the pump shunt is positioned between the distributed Raman amplifier and the signal input port.
6. The multi-stage optical amplifier of claim 1, wherein the first and second lengths of Raman amplifier fiber each have a length greater than or equal to 200m.
7. The multi-stage optical amplifier of claim 1, wherein the one or more pump wavelengths λ_p are in the range of 1300 to 1530 nm.
8. The multi-stage optical amplifier of claim 1, wherein the plurality of signal wavelengths λ_s is in the range of 1430 to 1530 nm.
9. The multi-stage optical amplifier of claim 1, wherein the first lossy member is an optical isolator.
10. The multi-stage optical amplifier of claim 1, wherein the first lossy member is an add/drop multiplexer.
11. The multi-stage optical amplifier of claim 1, wherein the first lossy member is a gain equalization member.
12. The multi-stage optical amplifier of claim 1, wherein the first lossy member is a dispersion compensation element.
13. The multi-stage optical amplifier of claim 1, wherein at least a portion of at least one of the first and second Raman amplifier fibers is a dispersion compensating fiber.
14. The multi-stage optical amplifier of claim 13, wherein at least a portion of the first and second Raman amplifier fibers are dispersion compensating fibers.
15. The multi-stage optical amplifier of claim 1, wherein the second length of amplifier fiber has a higher gain than the first length of amplifier fiber.

10005472-061802
2008190-2450007

16. The multi-stage optical amplifier of claim 3, further comprising:
at least one WDM coupler to couple a pump path from the signal input port to the
signal output port.

17. The multi-stage optical amplifier of claim 1, further comprising:
a pump source coupled to the pump input port.

18. The multi-stage optical amplifier of claim 1, further comprising:
at least one laser diode pump source coupled to the pump input port.

19. The multi-stage optical amplifier of claim 1, further comprising:
a second lossy member coupled to the pump shunt.

20. The multi-stage optical amplifier of claim 1, wherein the pump shunt includes
an optical fiber.

2008190-22450007

21. A multi-stage optical amplifier, comprising:

an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber configured to be coupled to a signal source that produces a plurality of signal wavelengths λ_s , and a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s , and an optical fiber cut-off wavelength of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber that is less than the one or more pump wavelengths λ_p ;

a signal input port coupled to the optical fiber;

a signal output port coupled to the optical fiber;

a pump input port coupled to the optical fiber;

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction; and

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber.

22. The multi-stage optical amplifier of claim 21, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

23. The multi-stage optical amplifier of claim 21, wherein the pump shunt is coupled to the signal input port and the signal output port.

24. The multi-stage optical amplifier of claim 21, wherein optical fiber cut-off wavelengths of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber are less than the one or more pump wavelengths λ_p .

25. The multi-stage optical amplifier of claim 21, further comprising:

a distributed Raman amplifier coupled to the signal input port.

26. The multi-stage optical amplifier of claim 25, wherein at least a portion of the pump shunt is positioned between the distributed Raman amplifier and the signal input port.

27. The multi-stage optical amplifier of claim [1]21, wherein the first and second lengths of Raman amplifier fiber each have a length greater than or equal to 200m.

28. The multi-stage optical amplifier of claim [1]21, wherein the one or more pump wavelengths λ_p are in the range of 1300 to 1530 nm.

29. The multi-stage optical amplifier of claim [1]21, wherein the plurality of signal wavelengths λ_s is in the range of 1430 to 1530 nm.

30. The multi-stage optical amplifier of claim [1]21, wherein the first lossy member is an optical isolator.

31. The multi-stage optical amplifier of claim [1]21, wherein the first lossy member is an add/drop multiplexer.

32. The multi-stage optical amplifier of claim [1]21, wherein the first lossy member is a gain equalization member.

33. The multi-stage optical amplifier of claim [1]21, wherein the first lossy member is a dispersion compensation element.

34. The multi-stage optical amplifier of claim [1]21, wherein at least a portion of at least one of the first and second Raman amplifier fibers is a dispersion compensating fiber.

35. The multi-stage optical amplifier of claim 34, wherein at least a portion of the first and second Raman amplifier fibers are dispersion compensating fibers.

36. The multi-stage optical amplifier of claim [1]21, wherein the second length of amplifier fiber has a higher gain than the first length of amplifier fiber.

37. The multi-stage optical amplifier of claim [1]21, further comprising:
at least one WDM coupler to couple a pump path from the signal input port to the
signal output port.

38. The multi-stage optical amplifier of claim [1]21, further comprising:
a pump source coupled to the pump input port.

39. The multi-stage optical amplifier of claim [1]21, further comprising:
at least one laser diode pump source coupled to the pump input port.

40. The multi-stage optical amplifier of claim [1]21, further comprising:
a second lossy member coupled to the pump shunt.

41. The multi-stage optical amplifier of claim [1]21, wherein the pump shunt
includes an optical fiber.

200542 061803
2008T90" 245000T

42. A multi-stage optical amplifier, comprising:

an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber configured to be coupled to a signal source that produces a plurality of signal wavelengths λ_s and a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s , wherein at least a portion of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is a dispersion compensating fiber;

a signal input port coupled to the optical fiber;

a signal output port coupled to the optical fiber;

a pump input port coupled to the optical fiber;

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction; and

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber.

43. The multi-stage optical amplifier of claim 42, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

44. The multi-stage optical amplifier of claim 42, wherein an optical fiber cut-off wavelength of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is less than the one or more pump wavelengths λ_p .

45. The multi-stage optical amplifier of claim 42, wherein at least a portion of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber are dispersion compensating fibers.

46. The multi-stage optical amplifier of claim 42, wherein the dispersion compensating fiber has a magnitude of dispersion of at least 50 psec/(nm) (km) for at least a portion of the plurality of signal wavelengths λ_s .

47. The multi-stage optical amplifier of claim 42, wherein the dispersion compensating fiber has a magnitude of dispersion less than 50 psec/(nm) (km) for at least a portion of the plurality of signal wavelengths λ_s .

48. The multi-stage optical amplifier of claim 42, further comprising:
a distributed Raman amplifier coupled to the signal input port.

49. The multi-stage optical amplifier of claim 48, wherein at least a portion of the pump shunt is positioned between the distributed Raman amplifier and the signal input port.

20250527 10:05:47.2061803

50. A multi-stage optical amplifier, comprising:
an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber configured to be coupled to a signal source that produces a plurality of signal wavelengths λ_s and a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s ;

a signal input port coupled to the optical fiber;

a signal output port coupled to the optical fiber;

a pump input port coupled to the optical fiber;

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction;

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber; and

at least a first pump source coupled to pump input port, the at least first pump source including multiple pump sources with outputs that are combined using at least one of wavelength and polarization multiplexing.

51. The multi-stage optical amplifier of claim 50, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

52. The multi-stage optical amplifier of claim 50, wherein the pump shunt is coupled to the signal input port and the signal output port.

53. The multi-stage optical amplifier of claim 50, wherein the at least first pump source includes multiple pump sources with outputs that are combined using wavelength and polarization multiplexing.

54. The multi-stage optical amplifier of claim 50, further comprising:
a distributed Raman amplifier coupled to the signal input port.

55. The multi-stage optical amplifier of claim 54, wherein at least a portion of the pump shunt is positioned between the distributed Raman amplifier and the signal input port.

20250722 100542.061802

56. A multi-stage optical amplifier system, comprising:
a plurality of transmitters that produce a plurality of signal wavelengths λ_s ;
a multi-stage optical amplifier including,
an optical fiber with a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber coupled to the plurality of transmitters and configured to be coupled to a pump source that produces one or more pump wavelengths λ_p , wherein the one or more pump wavelengths λ_p are less than at least a portion of the plurality of signal wavelengths λ_s , at least a portion of the plurality of wavelengths λ_s , of the first Raman amplifier fiber having an optical noise figure of less than 8 dB and less than an optical noise figure of the second Raman amplifier fiber, and at least a portion of the plurality of signal wavelengths λ_s , of the second Raman amplifier fiber having a gain level of at least 5 dB;
a signal input port coupled to the optical fiber,
a signal output port coupled to the optical fiber;
a pump input port coupled to the optical fiber;
a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction,
a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber; and
a plurality of receivers coupled to the multi-stage optical amplifier.

57. The multi-stage optical amplifier system of claim 56, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

58. The multi-stage optical amplifier system of claim 56, wherein the pump shunt is coupled to the signal input port and the signal output port.

59. The multi-stage optical amplifier system of claim 56, further comprising:
a distributed Raman amplifier coupled to the signal input port.

60. The multi-stage optical amplifier system of claim 59, wherein at least a portion of the pump shunt is positioned between the distributed Raman amplifier and the signal input port.

61. The multi-stage optical amplifier system of claim 56, wherein the multi-stage optical amplifier is an in-line amplifier.

62. The multi-stage optical amplifier system of claim 56, wherein the multi-stage optical amplifier is a booster amplifier.

63. The multi-stage optical amplifier system of claim 56, wherein the multi-stage optical amplifier is a pre-amplifier.

64. The multi-stage optical amplifier system of claim 56, wherein the plurality of receivers are directly coupled to the multi-stage optical amplifier.

10005472-061802
2008F90-22450001

65. A multi-stage optical amplifier system, comprising:
a plurality of transmitters that produce a plurality of signal wavelengths λ_s ;
a multi-stage optical amplifier, including,
an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber coupled to the plurality of ~~[transmitters]~~transmitters and configured to be coupled to a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s , and an optical fiber cut-off wavelength of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber that is less than the one or more pump wavelengths λ_p ,
a signal input port coupled to the optical fiber,
a signal output port coupled to the optical fiber,
a pump input port coupled to the optical fiber,
a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction,
a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber; and
a plurality of receivers coupled to the multi-stage optical amplifier.

66. The multi-stage optical amplifier system of claim 65, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

67. The multi-stage optical amplifier system of claim 65, wherein the pump shunt is coupled to the signal input port and the signal output port.

68. The multi-stage optical amplifier system of claim 65, wherein optical fiber cut-off wavelengths of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber are less than the one or more pump wavelengths λ_p .

69. The multi-stage optical amplifier system of claim 65, further comprising:
a distributed Raman amplifier coupled to the signal input port.

70. The multi-stage optical amplifier system of claim 69, wherein at least a
portion of the pump shunt is positioned between the distributed Raman amplifier and the
signal input port.

71. The multi-stage optical amplifier system of claim 69, wherein the multi-stage
optical amplifier is an in-line amplifier.

72. The multi-stage optical amplifier system of claim 69, wherein the multi-stage
optical amplifier is a booster amplifier.

73. The multi-stage optical amplifier system of claim 69, wherein the multi-stage
optical amplifier is a pre-amplifier.

74. The multi-stage optical amplifier system of claim 69, wherein the plurality of
receivers are directly coupled to the multi-stage optical amplifier.

10005472-061802
2008190-2450001

75. A multi-stage optical amplifier system, comprising:

a plurality of transmitters that produce a plurality of signal wavelengths λ_s ;
a multi-stage optical amplifier including,

an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber coupled to the plurality of transmitters and configured to be coupled to a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s , wherein at least a portion of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is a dispersion compensating fiber,

a signal input port coupled to the optical fiber,

a signal output port coupled to the optical fiber,

a pump input port coupled to the optical fiber,

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction,

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber; and

a plurality of receivers coupled to the multi-stage optical amplifier.

76. The multi-stage optical amplifier system of claim 75, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

77. The multi-stage optical amplifier system of claim 75, wherein an optical fiber cut-off wavelength of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is less than the one or more pump wavelengths λ_p .

78. The multi-stage optical amplifier system of claim 75, wherein at least a portion of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber are dispersion compensating fibers.

79. The multi-stage optical amplifier system of claim 75, wherein the dispersion compensating fiber has a magnitude of dispersion greater than 50 psec/(nm) ·(km) for at least a portion of the plurality of signal wavelengths λ_s .

80. The multi-stage optical amplifier system of claim 75, wherein the dispersion compensating fiber has a magnitude of dispersion less than, 50 psec/(nm) (km) for at least a portion of the plurality of signal wavelengths λ_s .

81. The multi-stage optical amplifier system of claim 75, further comprising:
a distributed Raman amplifier coupled to the signal input port.

82. The multi-stage optical amplifier system of claim 81, wherein at least a portion of the pump shunt is positioned between the distributed Raman amplifier and the signal input port.

83. The multi-stage optical amplifier system of claim 75, wherein the multi-stage optical amplifier is an in-line amplifier.

84. The multi-stage optical amplifier system of claim 75, wherein the multi-stage optical amplifier is a booster amplifier.

85. The multi-stage optical amplifier system of claim 75, wherein the multi-stage optical amplifier is a pre-amplifier.

86. The multi-stage optical amplifier system of claim 75, wherein the plurality of receivers are directly coupled to the multi-stage optical amplifier.

10005472-061802

87. A multi-stage optical amplifier system, comprising:

a plurality of transmitters that produce a plurality of signal wavelengths λ_s ;
a multi-stage optical amplifier including,

an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber coupled to the plurality of transmitters and configured to be coupled to a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s ,

a signal input port coupled to the optical fiber,

a signal output port coupled to the optical fiber,

a pump input port coupled to the optical fiber,

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction,

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber,

at least a first pump source coupled to pump input port, the at least first pump source including multiple pump sources with outputs that are combined using at least one of wavelength and polarization multiplexing; and

a plurality of receivers coupled to the multi-stage optical amplifier.

88. The multi-stage optical amplifier system of claim 87, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

89. The multi-stage optical amplifier system of claim 87, wherein the pump shunt is coupled to the signal input port and the signal output port.

90. The multi-stage optical amplifier system of claim 87, wherein at least first pump source includes multiple pump sources with outputs that are combined using wavelength and polarization multiplexing.

91. The multi-stage optical amplifier system of claim 87, further comprising:
a distributed Raman amplifier coupled to the signal input port.

92. The multi-stage optical amplifier system of claim 91, wherein at least a
portion of the pump shunt is positioned between the distributed Raman amplifier and the
signal input port.

93. The multi-stage optical amplifier system of claim 87, wherein the multi-stage
optical amplifier is an in-line amplifier.

94. The multi-stage optical amplifier system of claim 87, wherein the multi-stage
optical amplifier is a booster amplifier.

95. The multi-stage optical amplifier system of claim 87, wherein the multi-stage
optical amplifier is a pre-amplifier.

96. The multi-stage optical amplifier system of claim 87, wherein the plurality of
receivers are directly coupled to the multi-stage optical amplifier.

10005472-061802
2008T90" 27450001

97. A multi-stage optical amplifier, comprising:

an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber configured to be coupled to a signal source that produces a plurality of signal wavelengths λ_s and a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s , wherein at least a portion of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is a fiber with a selected small effective core area and high germanium doping to provide an enhancement of a Raman gain coefficient;

a signal input port coupled to the optical fiber;

a signal output port coupled to the optical fiber;

a pump input port coupled to the optical fiber;

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction; and

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber.

98. The multi-stage optical amplifier of claim 97, wherein the pump input port is positioned between the first and second lengths of Raman amplifier fiber.

99. The multi-stage optical amplifier of claim 97, wherein an optical fiber cut-off wavelength of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is less than the one or more pump wavelengths λ_p .

100. The multi-stage optical amplifier of claim 97, wherein at least a portion of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is a dispersion compensating fiber.

10005472-061802
2008190-245001

101. The multi-stage optical amplifier of claim 97, wherein at least a portion of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is a dispersion compensating fiber.

208T90" 2245000F

102. A multi-stage optical amplifier system, comprising:

a plurality of transmitters that produce a plurality of signal wavelengths λ_s ;

a multi-stage optical amplifier including,

an optical fiber including a first length of Raman amplifier fiber and a second length of Raman amplifier fiber, the optical fiber coupled to the plurality of transmitters and configured to be coupled to a pump source that produces one or more pump wavelengths λ_p , the one or more pump wavelengths λ_p being less than at least a portion of the plurality of signal wavelengths λ_s , wherein at least a portion of at least one of the first length of Raman amplifier fiber and the second length of Raman amplifier fiber is a fiber with a selected small effective core area and high germanium doping to provide an enhancement of a Raman gain coefficient,

a signal input port coupled to the optical fiber,

a signal output port coupled to the optical fiber,

a pump input port coupled to the optical fiber,

a first lossy member coupled to the optical fiber and positioned between the first and second lengths of Raman amplifier fiber, the first lossy member being lossy in at least one direction,

a pump shunt coupled to the optical fiber, wherein at least a portion of the one or more pump wavelengths λ_p is coupled between the first length of Raman amplifier fiber and the second length of Raman amplifier fiber; and

a plurality of receivers coupled to the multi-stage optical amplifier.

2008F90" 2245000T